

PRODUCTION DESCRIPTION

Created by coating white ink-jet to transparent polyester raw materials and optimized for the lighting advertisement. Used for the close-range advertisements mainly. Ideal for durable scratch-resistant backlit displays in high traffic locations.

FEATURES AND APPLICATIONS

- Excellent ink fixation
- Superior image quality and illuminance
- Unique fast-drying formulation that makes it a top-quality solution for a range of full-color needs.
- High level of durability and excellent surface hardness
- Compatible with an extensive array of Solvent and Eco Solvent printers
- Wide colors for lighting, subway wall advertisement, shelter advertisement and department store POP

GENERAL AVAILABILITY

42 inches (1.05 meters) x 30M Roll Type
50 inches (1.27 meters) x 30M
54 inches (1.37 meters) x 30M
60 inches (1.52 meters) x 30M

TECHNICAL DATA

Base Film 10mil Clear PET
Color & Finish White Gloss/Matt

PHYSICAL PROPERTIES

Total Caliper	12mil / 285micron
Grammage	295g/m ²
Opacity(Transmission)	70%
Whiteness	92%
Film Gloss	95(at 60°)
Water fastness	Good water resistance
Operating Condition	59°F to 95°F (20~70% RH)
Recommended Storage Conditions	77°F (25°C), 50% RH
Shelf Life Expectancy	2 years
Outdoor Durability	3 years

PRINTER AND INK COMPATIBILITY

Compatible with Echo-Solvent or Mild Solvent as well as Pure Solvent inks. Especially fixed for Echo-Solvent ink.

RoHS Certification

- PSA & PVC that make up this products are already certificated by KTR about RoHS. KTR(Korea Testing & Research Institute) is recognized by international standards.
- Testing method -KS M 0032, KS M0016 & US EPA 8270D

Specification and details are offered in good faith but will not be accepted in matters of warranty.

For updated technical specifications, please refer to data sheets on our internet site www.kcsltd.co.kr